

SECTION HRN
HORNA
B
C
D
E**CONTENTS**

PRECAUTION	2	HORN	3
PRECAUTIONS	2	Wiring Diagram	3
Supplemental Restraint System (SRS) AIR BA			
G and SEAT BELT PRE-TENSIONER	2		
Battery Service	2		
COMPONENT DIAGNOSIS	3	ON-VEHICLE REPAIR	7
		HORN	7
		Removal and Installation	7

F
G
H
I
J
K

HRN

M
N
O
P

PRECAUTIONS

< PRECAUTION >

PRECAUTION

PRECAUTIONS

Supplemental Restraint System (SRS) AIR BAG and SEAT BELT PRE-TENSIONER

INFOID:0000000000994407

The Supplemental Restraint System such as "AIR BAG" and "SEAT BELT PRE-TENSIONER", used along with a front seat belt, helps to reduce the risk or severity of injury to the driver and front passenger for certain types of collision. This system includes seat belt switch inputs and dual stage front air bag modules. The SRS system uses the seat belt switches to determine the front air bag deployment, and may only deploy one front air bag, depending on the severity of a collision and whether the front occupants are belted or unbelted. Information necessary to service the system safely is included in the SRS and SB section of this Service Manual.

WARNING:

- To avoid rendering the SRS inoperative, which could increase the risk of personal injury or death in the event of a collision which would result in air bag inflation, all maintenance must be performed by an authorized NISSAN/INFINITI dealer.
- Improper maintenance, including incorrect removal and installation of the SRS, can lead to personal injury caused by unintentional activation of the system. For removal of Spiral Cable and Air Bag Module, see the SRS section.
- Do not use electrical test equipment on any circuit related to the SRS unless instructed to in this Service Manual. SRS wiring harnesses can be identified by yellow and/or orange harnesses or harness connectors.

Battery Service

INFOID:0000000000994408

HORN

< COMPONENT DIAGNOSIS >


COMPONENT DIAGNOSIS

HORN

Wiring Diagram

INFOID:0000000000994409

■ : DATA LINE



HORN


ALMWA0011GE

HRN-3

HORN

< COMPONENT DIAGNOSIS >

HORN CONNECTORS



Terminal No.	Color of Wire	Signal Name
24	25	26, 27
31	32	33, 34

Terminal No.	Color of Wire	Signal Name
79	77	76, 75, 74, 73, 72, 71
99	98	97, 96, 95, 94, 93, 92, 91
70	69	68, 67, 66, 65, 64, 63, 62, 61, 60
90	89	88, 87, 86, 85, 84, 83, 82, 81, 80

Terminal No.	Color of Wire	Signal Name
78	P	CAN-L
79	L	CAN-H

Terminal No.	Color of Wire	Signal Name
34	LW	HORN

Terminal No.	Color of Wire	Signal Name
32	41	39
46	45	44, 43

Terminal No.	Color of Wire	Signal Name
1	2	3
4	5	6, 7, 8


Terminal No.	Color of Wire	Signal Name
39	P	CAN-L
40	L	CAN-H
41	B	S-GND
44	GW	HORN_RLY
45	L/O	HORN_SW

HORN

< COMPONENT DIAGNOSIS >

HORN CONNECTORS

Connector No.	E18
Connector Name	IPDM ER (INTELLIGENT POWER DISTRIBUTION MODULE ENGINE ROOM)
Connector Color	WHITE




Connector No.	E21
Connector Name	JOINT CONNECTOR-E03
Connector Color	WHITE


Terminal No.	Color of Wire	Signal Name
1	L	—
2	L	—

Terminal No.	Color of Wire	Signal Name
1	P	—
2	L	—
3	LW	—

Connector No.	E30
Connector Name	WIRE TO WIRE
Connector Color	WHITE



Connector No.	E22
Connector Name	JOINT CONNECTOR-E04
Connector Color	WHITE



Terminal No.	Color of Wire	Signal Name
1	L	—
2	L	—

Terminal No.	1	2
Color of Wire	P	P
Signal Name	—	—

ALMIA0053GB

A B C D E F G H I J K L M N P Q R S T U V Z O

HORN

< COMPONENT DIAGNOSIS >

HORN CONNECTORS


Connector No.	E216
Connector Name	HORN
Connector Color	BLACK



Connector No.	E215
Connector Name	HORN
Connector Color	BLACK



Connector No.	E202
Connector Name	WIRE TO WIRE
Connector Color	WHITE



Terminal No.	Color of Wire	Signal Name
1	G	G

Terminal No.	Color of Wire	Signal Name
1	G	G
2	—	—

Terminal No.	Color of Wire	Signal Name
1	G	G
2	—	—
3	—	—

Terminal No.	Color of Wire	Signal Name
1	G	G

Terminal No.	Color of Wire	Signal Name
1	G	G
2	—	—

Terminal No.	Color of Wire	Signal Name
1	G	G
2	—	—
3	—	—

Connector No.	H-1
Connector Name	HORN RELAY
Connector Color	BLACK



Terminal No.	Color of Wire	Signal Name
1	GW	—
2	G/B	—
3	G	—

HORN

< ON-VEHICLE REPAIR >

ON-VEHICLE REPAIR


HORN

Removal and Installation

INFOID:0000000000994410

REMOVAL

1. Position aside the front fender protector LH. Refer to [EXT-18, "Removal and Installation"](#).
2. Disconnect the horn connectors (A).
3. Remove the horn bracket bolt (B), and remove horn (2) and horn (1).



INSTALLATION

Installation is in the reverse order of removal.

A

B

C

D

E

F

G

H

I

J

K

HRN

M

N

O

P