

Edition: August 2002
 Revision: November 2002
 Publication No. SM2E-1B15U2

QUICK REFERENCE INDEX

**NISSAN
 SENTRA**
 MODEL B15 SERIES

A GENERAL INFORMATION	GI General Information	
B ENGINE	EM Engine Mechanical	
	LU Engine Lubrication System	
	CO Engine Cooling System	
	EC Engine Control System	
	FL Fuel System	
	EX Exhaust System	
	ACC Accelerator Control System	
C TRANSMISSION/ TRANSAXLE	CL Clutch	
	MT Manual Transaxle	
	AT Automatic Transaxle	
D DRIVELINE/AXLE	FAX Front Axle	
	RAX Rear Axle	
E SUSPENSION	FSU Front Suspension	
	RSU Rear Suspension	
	WT Road Wheels & Tires	
F BRAKES	BR Brake System	
	PB Parking Brake System	
	BRC Brake Control System	
G STEERING	PS Power Steering System	
H RESTRAINTS	SB Seat Belts	
	SRS Supplemental Restraint System (SRS)	
	BL Body, Lock & Security System	
I BODY	GW Glasses, Window System & Mirrors	
	RF Roof	
	EI Exterior & Interior	
	IP Instrument Panel	
	SE Seat	
	J AIR CONDITIONER	MTC Manual Air Conditioner
	K ELECTRICAL	SC Starting & Charging System
LT Lighting System		
DI Driver Information System		
WW Wiper, Washer & Horn		
BCS Body Control System		
LAN LAN System		
AV Audio Visual & Telephone System		
ACS Auto Cruise Control System		
PG Power Supply, Ground & Circuit Elements		
L MAINTENANCE		MA Maintenance
M INDEX	IDX Alphabetical Index	

A
B
C
D
E
F
G
H
I
J
K
L
M

FOREWORD

This manual contains maintenance and repair procedures for the 2002 NISSAN SENTRA.

In order to assure your safety and the efficient functioning of the vehicle, this manual should be read thoroughly. It is especially important that the PRECAUTIONS in the GI section be completely understood before starting any repair task.

All information in this manual is based on the latest product information at the time of publication. The right is reserved to make changes in specifications and methods at any time without notice.

IMPORTANT SAFETY NOTICE

The proper performance of service is essential for both the safety of the technician and the efficient functioning of the vehicle.

The service methods in this Service Manual are described in such a manner that the service may be performed safely and accurately. Service varies with the procedures used, the skills of the technician and the tools and parts available. Accordingly, anyone using service procedures, tools or parts which are not specifically recommended by NISSAN must first be completely satisfied that neither personal safety nor the vehicle's safety will be jeopardized by the service method selected.



NISSAN NORTH AMERICA, INC.
Technical Publications Department
Gardena, California



PLEASE HELP MAKE THIS SERVICE MANUAL BETTER!

Your comments are important to NISSAN and will help us to improve our Service Manuals. Use this form to report any issues or comments you may have regarding our Service Manuals. Please print this form and type or write your comments below. Mail or fax to:

Nissan North America, Inc.
Technical Service Information
39001 Sunrise Drive, P.O. Box 9200
Farmington Hills, MI USA 48331
FAX: (248) 488-3910

SERVICE MANUAL: Model: _____ **Year:** _____

PUBLICATION NO. (Please photocopy back cover): _____

VEHICLE INFORMATION VIN: _____ **Production Date:** _____

Please describe any issues or problems in detail:

Page number(s) _____ *Note: Please include a copy of each page, marked with your comments.*

Are the trouble diagnosis procedures logical and easy to use? (circle your answer) YES NO

If no, what page number(s)? _____ *Note: Please include a copy of each page, marked with your comments.*

Please describe the issue or problem in detail: _____

Is the organization of the manual clear and easy to follow? (circle your answer) YES NO

Please comment: _____

What information should be included in NISSAN Service Manuals to better support you in servicing or repairing customer vehicles?

DATE: _____ YOUR NAME: _____ POSITION: _____

DEALER: _____ DEALER NO.: _____ ADDRESS: _____

CITY: _____ STATE/PROV./COUNTRY: _____ ZIP/POSTAL CODE: _____

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 1.8L, QG ENGINE)

2002

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 1.8L, QG ENGINE)

PFP:00027

Engine Tune-Up Data

ELS000L4

Engine	QG18DE	
Classification	Gasoline	
Cylinder arrangement	4, in-line	
Displacement cm ³ (cu in)	1,769 (107.94)	
Bore × stroke mm (in)	80.0 x 88.0 (3.150 x 3.465)	
Valve arrangement	DOHC	
Firing order	1-3-4-2	
Number of piston rings	Compression	2
	Oil	1
Number of main bearings	5	
Compression ratio	9.5	

Drive Belt Deflection and Tension

Component		Deflection Adjustment Unit: mm (in)			Tension Adjustment *1 Unit: N (kg, lb)		
		Used Belt		New Belt	Used Belt		New Belt
		Limit	After Adjustment		Limit	After Adjustment	
Generator	With air conditioner compressor	8.1 (0.319)	5.3 - 5.7 (0.209 - 0.244)	4.5 - 5.0 (0.177 - 0.197)	292 (30, 66)	652 - 740 (66.5 - 75.5, 146.6 - 166.4)	789 - 877 (80.5 - 89.5, 177.4 - 197.1)
	Without air conditioner compressor	10.2 (0.402)	6.5 - 7.0 (0.256 - 0.276)	5.5 - 6.1 (0.217 - 0.240)	292 (30, 60)	652 - 740 (66.5 - 75.5, 146.6 - 166.4)	789 - 877 (80.5 - 89.5, 177.4 - 197.1)
Power steering oil pump		7.1 (0.280)	4.4 - 4.9 (0.173 - 0.193)	3.9 - 4.4 (0.154 - 0.173)	196 (20, 44)	495 - 583 (50.5 - 59.5, 111.4 - 131.2)	603 - 691 (61.5 - 70.5, 135.6 - 155.5)
Applied pushing force		98 N (10 kg, 22 lb)			—		

*1: If the belt tension gauge cannot be installed at check points shown, check belt tension at a different location on the belt.

Spark Plugs (Double Platinum - Tipped)

Type	Standard	PLFR5A-11
	Hot	PLFR4A-11
	Cold	PLFR6A-11
Plug gap	nominal 1.1 mm (0.043 in)	

Front Wheel Alignment (Unladen*1)

ELS000L6

Camber Degree minute (decimal degree)	Minimum	-1°10' (-1.17°)
	Nominal	-0°25' (-0.42°)
	Maximum	0°20' (0.33°)
	Left and right difference	45' (0.75°) or less
Caster Degree minute (decimal degree)	Minimum	0°51' (0.85°)
	Nominal	1°36' (1.60°)
	Maximum	2°21' (2.35°)
	Left and right difference	45' (0.75°) or less

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 1.8L, QG ENGINE)

2002

Kingpin inclination Degree minute (decimal degree)		Minimum	13°58' (13.97°)
		Nominal	14°43' (14.72°)
		Maximum	15°28' (15.47°)
Total toe-in	Distance mm (in)	Minimum	1 (0.039")
		Nominal	2 (0.079")
		Maximum	3 (0.118")
	Angle (left plus right) Degree minute (decimal degree)	Minimum	5.5' (0.08°)
		Nominal	11' (0.18°)
		Maximum	16' (0.27°)
Wheel turning angle Full turn*2	Inside Degree minute (decimal degree)	Minimum	34° (34.0°)
		Nominal	37° (37.0°)
		Maximum	38° (38.0°)
	Outside Degree minute (decimal degree)	Nominal	31° (31.0°)

*1: Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

*2: On power steering models, wheel turning force (at circumference of steering wheel) of 98 to 147 N (10 to 15 kg, 22 to 33 lb) with engine idle.

Rear Wheel Alignment (Unladen*)

ELS000L7

Camber Degree minute (decimal degree)		Minimum	-1°45' (-1.75°)
		Nominal	-1°00' (-1.00°)
		Maximum	-0°15' (-0.25°)
Total toe-in	Distance mm (in)	Minimum	-3 (-0.12)
		Nominal	1 (0.04)
		Maximum	5 (0.20)
	Angle (left plus right) Degree minute (decimal degree)	Minimum	-16' (-0.27°)
		Nominal	5'30" (0.09°)
		Maximum	26' (0.43°)

*: Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

Brake

ELS000L8

Unit: mm (in)

Front brake	Brake model	CL25VA
	Cylinder bore diameter	57.2 (2.252)
	Pad length × width × thickness	125.6 × 46.0 × 11.0 (4.94 × 1.811 × 0.433)
	Rotor outer diameter × thickness	257 × 22 (10.12 × 0.87)
Rear brake	Brake model	LT20G
	Cylinder bore diameter/caliper bore diameter	15.87 (5/8) type a 17.45 (11/16) type b
	Lining length × width × thickness	219.4 × 35 × 4.5 (8.64 × 1.38 × 0.177)
	Drum inner diameter/Disc diameter × thickness	203.2 (8)
Master cylinder	Cylinder bore diameter	23.81 (15/16)
Control valve	Valve model	Dual proportioning valve
	Split point [kPa (kg/cm ² , psi)] × reducing ratio	1,961 (20,284) × 0.2

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 1.8L, QG ENGINE)

2002

	Booster model	M215T
Brake booster	Diaphragm diameter	Primary: 230 (9.06) Secondary: 205 (8.07)
Brake fluid	Recommended brake fluid	DOT 3

Disc Brake - Repair Limits

Unit: mm (in)

Brake model	CL25VA
Pad wear limit Minimum thickness	2.0 (0.079)
Rotor repair limit Minimum thickness	20 (0.79)

Drum Brake - Repair Limits

Unit: mm (in)

Brake model	LT20G
Lining wear limit	Minimum thickness 1.5 (0.059)
Drum repair limit	Maximum inner diameter 204.5 (8.05)
	Maximum out-of round 0.03 (0.0012)

Refill Capacities

ELS000LC

Engine Coolant Capacity (Approximate)

Unit: ℓ (US qt, Imp qt)

Drain and refill without reservoir	M/T (RS5F70A)	6.0 (6 3/8, 5 1/4)
	A/T (RE4F03B)	5.9 (6 1/4, 5 1/4)
Reservoir tank (at MAX level)		0.7 (3/4, 5/8)

Engine Oil Capacity (Approximate)

Unit: ℓ (US qt, Imp qt)

Drain and refill	With oil filter change	2.7 (2 7/8, 2 3/8)
	Without oil filter change	2.5 (2 5/8, 2 1/4)
Dry engine (engine overhaul)		3.1 (3 1/4, 2 3/4)

Miscellaneous Capacities (Approximate)

System description	Metric measurement	US measurement	Imp measurement
Fuel tank	50 ℓ	13 1/4 gal	11 gal
Power steering system	1.0 ℓ	2 1/8 pt	1 3/4 pt
Transaxle	M/T (RS5F70A)	3.0 ℓ	3 1/8 qt
	A/T (RE4F03B)	7.0 ℓ	7 3/8 qt
Air conditioning system	refrigerant	0.45 - 0.55 kg	0.99 - 1.21 lb
	compressor oil	180 ml	6.1 fl oz

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 2.5L, QR ENGINE)

2002

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 2.5L, QR ENGINE)

PFP:00027

Engine Tune-Up Data

ELS000LF

Engine		QR25DE
Cylinder arrangement		4 in-line
Displacement cm ³ (cu in)		2,488 (151.82)
Bore and stroke mm (in)		89.0 x 100 (3.50 - 3.94)
Valve arrangement		DOHC
Firing order		1-3-4-2
Number of piston rings	Compression	2
	Oil	1
Compression ratio		9.5
Compression pressure kPa (kg/cm ² , psi) / 250 rpm	Standard	1,250 (12.8, 182)
	Minimum	1,060 (10.8, 154)
	Differential limit between cylinders	100 (1.0, 14)

Drive Belt Deflection and Tension

Tension of drive belts	Auto adjustment by auto-tensioner
------------------------	-----------------------------------

Spark Plugs (Double Platinum Tipped)

Type	Standard	PLFR5A-11
	Hot	PLFR4A-11
	Cold	PLFR6A-11
Plug gap		nominal 1.1 mm (0.043 in)

Front Wheel Alignment (Unladen*1)

ELS000LI

Camber Degree minute (decimal degree)	Minimum	-1°12' (-1.2°)	
	Nominal	-0°27' (-0.45°)	
	Maximum	0°18' (0.3°)	
	Left and right difference	45' (0.75°) or less	
Caster Degree minute (decimal degree)	Minimum	0°58' (0.97°)	
	Nominal	1°43' (1.72°)	
	Maximum	2°28' (2.47°)	
	Left and right difference	45' (0.75°) or less	
Kingpin inclination Degree minute (decimal degree)	Minimum	14°03' (14.05°)	
	Nominal	14°46' (14.77°)	
	Maximum	15°31' (15.52°)	
Total toe-in	Distance mm (in)	Minimum	1 (0.039")
		Nominal	2 (0.079")
		Maximum	3 (0.118")
	Angle (left plus right) Degree minute (decimal degree)	Minimum	5.5' (0.08°)
		Nominal	11' (0.18°)
		Maximum	16' (0.27°)

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 2.5L, QR ENGINE)

2002

Wheel turning angle Full turn*2	Inside Degree minute (decimal degree)	Minimum	29° (29.0°)
		Nominal	32° (32.0°)
		Maximum	33° (33.0°)
	Outside Degree minute (decimal degree)	Nominal	27° (27.0°)

*1: Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

*2: On power steering models, wheel turning force (at circumference of steering wheel) of 98 to 147 N (10 to 15 kg, 22 to 33 lb) with engine idle.

Rear Wheel Alignment (Unladen*)

ELS000LJ

Camber Degree minute (decimal degree)		Minimum	-1°45' (-1.75°)
		Nominal	-1°00' (-1.00°)
		Maximum	-0°15' (-0.25°)
Total toe-in	Distance mm (in)	Minimum	-3 (-0.12)
		Nominal	1 (0.04)
		Maximum	5 (0.20)
	Angle (left plus right) Degree minute (decimal degree)	Minimum	-16' (-0.27°)
		Nominal	5'30" (0.09°)
		Maximum	26' (0.43°)

*: Fuel, radiator coolant and engine oil full. Spare tire, jack, hand tools and mats in designated positions.

Brake

ELS000LK

Unit: mm (in)

Front brake	Brake model	CL25VB
	Cylinder bore diameter	57.2 (2.252)
	Pad length × width × thickness	125.6 × 46.0 × 11.0 (4.94 × 1.811 × 0.433)
	Rotor outer diameter × thickness	280 × 22 (11.02 × 0.87)
Rear brake	Brake model	CL9HC
	Cylinder bore diameter/caliper bore diameter	33.96 (1 11/32)
	Lining length × width × thickness	89.1 × 39.5 × 10 (3.508 × 1.555 × 0.39)
	Drum inner diameter/Disc diameter × thickness	258 × 9 (10.16 × 0.35)
Master cylinder	Cylinder bore diameter	23.81 (15/16)
Control valve	Valve model	Dual proportioning valve
	Split point [kPa (kg/cm ² , psi)] × reducing ratio	2,942 (30,427) × 0.2
Brake booster	Booster model	M215T
	Diaphragm diameter	Primary: 230 (9.06) Secondary: 205 (8.07)
Brake fluid	Recommended brake fluid	DOT 3

Disc Brake - Repair Limits

Unit: mm (in)

Brake model	CL25VB (Front)	CL9HC (Rear)
Pad wear limit Minimum thickness	2.0 (0.079)	2.0 (0.079)
Rotor repair limit Minimum thickness	20 (0.79)	8 (0.31)

QUICK REFERENCE CHART: SENTRA (EQUIPPED WITH 2.5L, QR ENGINE)

2002

ELS000LN

Refill Capacities

Engine Coolant Capacity (Approximate)

Unit: ℓ (US qt, Imp qt)

Drain and refill (without reservoir)	M/T (RS5F51A, RS6F51H)	6.0 (6 3/8, 5 1/4)
	A/T (RE4F04B)	5.9 (6 1/4, 5 1/4)
Reservoir tank (at MAX level)		0.7 (3/4, 5/8)

Engine Oil Capacity (Approximate)

Unit: ℓ (US qt, Imp qt)

Drain and refill	With oil filter change	4.2 (4 1/2, 3 3/4)
	Without oil filter change	4.0 (4 1/4, 3 1/2)
Dry engine (engine overhaul)		4.6 (4 7/8, 4)

Miscellaneous Capacity (Approximate)

System description		Metric measurement	US measurement	Imp measurement
Fuel tank		50 ℓ	13 1/4 gal	11 gal
Power steering system		1.0 ℓ	2 1/8 pt	1 3/4 pt
Transaxle	M/T (RS5F51A, RS6F51H)	2.3 ℓ	2 3/8 qt	2 qt
	A/T (RE4F04B)	8.5 ℓ	9 qt	7 1/2 qt
Air conditioning system	refrigerant	0.45 - 0.55 kg	0.99 - 1.21 lb	—
	compressor oil	180 ml	6.1 fl oz	6.3 fl oz

TEST VALUE AND TEST LIMIT (GST ONLY — NOT APPLICABLE TO CONSULT-II)

The following is the information specified in Mode 6 of SAE J1979.

The test value is a parameter used to determine whether a system/circuit diagnostic test is "OK" or "NG" while being monitored by the ECM during self-diagnosis. The test limit is a reference value which is specified as the maximum or minimum value and is compared with the test value being monitored.

Items for which these data (test value and test limit) are displayed are the same as SRT code items.

These data (test value and test limit) are specified by Test ID (TID) and Component ID (CID) and can be displayed on the GST screen.

SRT item	Self-diagnostic test item	DTC	Test value (GST display)		Test limit	Conversion
			TID	CID		
CATALYST	Three way catalyst function (Bank 1)	P0420	01H	01H	Max.	1/128
		P0420	02H	81H	Min.	1
	Three way catalyst function (Bank 2)	P0430	03H	02H	Max.	1/128
		P0430	04H	82H	Min.	1
EVAP SYSTEM	EVAP control system (Small leak)	P0442	05H	03H	Max.	1/128mm ²
		P1442	05H	03H	Max.	1/128mm ²
	EVAP control system purge flow monitoring	P0441	06H	83H	Min.	20mV
	EVAP control system (Very small leak)	P0456	07H	03H	Max.	1/128mm ²
P1456		07H	03H	Max.	1/128mm ²	
HO2S	Heated oxygen sensor 1 (Bank 1)	P0133	09H	04H	Max.	16ms
		P1143	0AH	84H	Min.	10mV
		P1144	0BH	04H	Max.	10mV
		P0132	0CH	04H	Max.	10mV
	Heated oxygen sensor 1 (Bank 2)	P0134	0DH	04H	Max.	1s
		P0153	11H	05H	Max.	16ms
		P1163	12H	85H	Min.	10mV
		P1164	13H	05H	Max.	10mV
	Heated oxygen sensor 2 (Bank 1)	P0152	14H	05H	Max.	10mV
		P0154	15H	05H	Max.	1s
		P0139	19H	86H	Min.	10mV/500ms
		P1147	1AH	86H	Min.	10mV
	Heated oxygen sensor 2 (Bank 2)	P1146	1BH	06H	Max.	10mV
		P0138	1CH	06H	Max.	10mV
		P0159	21H	87H	Min.	10mV/500ms
		P1167	22H	87H	Min.	10mV
HO2S HTR	Heated oxygen sensor 1 heater (Bank 1)	P0032	29H	08H	Max.	20mV
		P0031	2AH	88H	Min.	20mV
	Heated oxygen sensor 1 heater (Bank 2)	P0052	2BH	09H	Max.	20mV
		P0051	2CH	89H	Min.	20mV
	Heated oxygen sensor 2 heater (Bank 1)	P0038	2DH	0AH	Max.	20mV
		P0037	2EH	8AH	Min.	20mV
	Heated oxygen sensor 2 heater (Bank 2)	P0058	2FH	0BH	Max.	20mV
		P0057	30H	8BH	Min.	20mV
EGR SYSTEM	EGR function	P0400	31H	8CH	Min.	1°C
		P0400	32H	8CH	Min.	1°C
		P0400	33H	8CH	Min.	1°C
		P0400	34H	8CH	Min.	1°C
		P1402	35H	0CH	Max.	1°C

TEST VALUE AND TEST LIMIT (GST ONLY — NOT APPLICABLE TO CONSULT-II)

The following is the information specified in Mode 6 of SAE J1979.

The test value is a parameter used to determine whether a system/circuit diagnostic test is “OK” or “NG” while being monitored by the ECM during self-diagnosis. The test limit is a reference value which is specified as the maximum or minimum value and is compared with the test value being monitored.

Items for which these data (test value and test limit) are displayed are the same as SRT code items.

These data (test value and test limit) are specified by Test ID (TID) and Component ID (CID) and can be displayed on the GST screen.

SRT item	Self-diagnostic test item	DTC	Test value (GST display)		Test limit	Conversion
			TID	CID		
CATALYST	Three way catalyst function	P0420	01H	01H	Max.	1/128
		P0420	02H	81H	Max.	1
EVAP SYSTEM	EVAP control system (Small leak)	P0442	05H	03H	Max.	1/128mm ²
		P1442	05H	03H	Max.	1/128mm ²
	EVAP control system purge flow monitoring	P0441	06H	83H	Min.	20mV
HO2S	A/F sensor 1	P1273	43H	0EH	Max.	0.002
		P1274	44H	8EH	Min.	0.002
		P1275	45H	8EH	Min.	0.004
	Heated oxygen sensor 2	P0139	19H	86H	Min.	10mV/500ms
		P1147	1AH	86H	Min.	10mV
		P1146	1BH	06H	Max.	10mV
	Heated oxygen sensor 3	P0138	1CH	06H	Max.	10mV
		P0145	61H	92H	Min.	10mV/500ms
		P0144	62H	92H	Min.	10mV
		P0143	63H	12H	Max.	10mV
		P0146	64H	12H	Max.	10mV
	HO2S HTR	A/F sensor 1 heater	P1277	57H	04H	Max.
P1277			58H	04H	Min.	5mV
Heated oxygen sensor 2 heater		P0141	2DH	0AH	Max.	20mV
		P0141	2EH	8AH	Min.	20mV
Heated oxygen sensor 3 heater		P0147	71H	14H	Max.	20mV
		P0147	72H	94H	Min.	20mV
EGR SYSTEM	EGR function	P0400	31H	8CH	Min.	1°C
		P0400	32H	8CH	Min.	1°C
		P0400	33H	8CH	Min.	1°C
		P0400	34H	8CH	Min.	1°C
		P1402	35H	0CH	Max.	1°C

TEST VALUE AND TEST LIMIT (GST ONLY — NOT APPLICABLE TO CONSULT-II)

The following is the information specified in Mode 6 of SAE J1979.

The test value is a parameter used to determine whether a system/circuit diagnostic test is “OK” or “NG” while being monitored by the ECM during self-diagnosis. The test limit is a reference value which is specified as the maximum or minimum value and is compared with the test value being monitored.

These data (test value and test limit) are specified by Test ID (TID) and Component ID (CID) and can be displayed on the GST screen.

SRT item	Self-diagnostic test item	DTC	Test value (GST display)		Test limit	Conversion
			TID	CID		
CATALYST	Three way catalyst function	P0420	01H	01H	Max.	1/128
		P0420	02H	81H	Min.	1
EVAP SYSTEM	EVAP control system (Small leak)	P0442	05H	03H	Max.	1/128mm ²
	EVAP control system purge flow monitoring	P0441	06H	83H	Min.	20mV
	EVAP control system (Very small leak)	P0456	07H	03H	Max.	1/128mm ²
		P1456	07H	03H	Max.	1/128mm ²
HO2S	Heated oxygen sensor 1	P0133	09H	04H	Max.	16ms
		P1143	0AH	84H	Min.	10mV
		P1144	0BH	04H	Max.	10mV
		P0132	0CH	04H	Max.	10mV
	Heated oxygen sensor 2	P0134	0DH	04H	Max.	1s
		P0139	19H	86H	Min.	10mV/500ms
		P1147	1AH	86H	Min.	10mV
		P1146	1BH	06H	Max.	10mV
HO2S HTR	Heated oxygen sensor 1 heater	P0138	1CH	06H	Max.	10mV
		P0032	29H	08H	Max.	20mV
	Heated oxygen sensor 2 heater	P0031	2AH	88H	Min.	20mV
		P0038	2DH	0AH	Max.	20mV
		P0037	2EH	8AH	Min.	20mV